

| | |
|------------------------------|---|
| FEATURES | NOC for Ceiling is the high quality of 100% acrylic emulsion. It is special for ceiling applications on plaster or gypsum board ceiling. Matt finishing is designed to conceal ceiling joints by reducing reflection on film finishing in order to provide smooth seamless ceiling surfaces and excellent adhesion. Anti-fungus and algae. Free from lead and mercury. It is ideal for application to gypsum on the ceiling. |
| TECHNICAL INFORMATION | <p>Type: 100% Acrylic Emulsion</p> <p>Color: White, Grey</p> <p>Film appearance: Matt</p> <p>Pack size: 1 and 5 Gallons</p> <p>Solid by volume: 31</p> <p>Solid by weight: 49-52</p> <p>Specific gravity: 1.440-1.500</p> <p>Wet film thickness: 95-110 microns</p> <p>Dry film thickness: 30-34 microns</p> <p>Theoretical coverage: 35-40 Sq.m./coat/gallon</p> <p>Remark - Actual Surface coverage will depend on surface irregularities, Mixing, Application Condition method and technique; as well as the structure and dimensions of the object to be coated</p> <p>Touch dry (25-30°C): 30 Minutes</p> <p>Recoat dry (25-30°C): 2 Hours</p> <p>Full cure (25-30°C): At least 7 Days</p> |
| APPLICATION | <p>Tools: Roller, Brush and Spray</p> <p>Diluent: Clean Water</p> <p>Dilution (%): 5-10% (roller and brush) / 15-20% (spray)</p> |
| APPLICATION SYSTEM | <p>Surface Preparation</p> <p>New Surface: The surfaces must be completely dried and cured at least 1 month. Surface must be free from efflorescence. Brush down or scrape off any loose material and cement splashes.</p> <p>Old Surface: Powdery and chalky surfaces must be scrubbed and cleaned with water. Fungus and Mildew growth must be clean off with hypochlorite solution and allow for drying out at least 2-3 days.</p> <p>Coating system</p> <p>Primer: New Surface: Apply 1-2 coats of NOC Super Primer two in one NO2012 (Water-based) Old Surface: Apply 1-2 coats of NOC Super Primer two in one NO2012 (Water-based)</p> <p>Topcoat: Apply 1-2 coats of NOC Ceiling Paint</p> |
| TIS | - |
| HANDLING AND STORAGE | Keep the containers in a dry, cool, well ventilated space and away from heat. Containers must be kept tightly closed. |
| HEALTH AND SAFETY | Use under well ventilated conditions. Avoid skin contact. |