

<b>FEATURES</b>	HATO Fiber cement Paint is formulated from 100% pure acrylic emulsion, special quality color pigments. It protects fiber cement board from UV light. Paint film is highly flexible, prevents water penetration, anti-mold, anti-fungus and algae. It is easy to apply, fast-drying and highly adhesive with fiber cement board.
<b>TECHNICAL INFORMATION</b>	
Type	100% Pure Acrylic Emulsion Paint
Color	Wide range of colours. Please refer to Hato Paint Catalogue
Film appearance	Semi-gloss
Pack size	1 US Gallons
Solid by volume	24-28 %
Solid by weight	30-38 %
Flash point	N/A
Volatile organic compounds (VOCs)	N/A
Wet film thickness	95-110 microns
Dry film thickness	23-31 microns
Theoretical coverage	35-40 Sq.m./coat/gallon
	Remark - Actual Surface coverage will depend on surface irregularities, Mixing, Application Condition method and technique; as well as the structure and dimensions of the object to be coated
Touch dry (25-30°C)	30 Minutes
Recoat dry (25-30°C)	2 Hours
Full cure (25-30°C)	At least 7 Days
<b>APPLICATION</b>	
Tools	Roller, Brush and Spray
Diluent	Clean Water
Dilution (%)	5-10% (roller and brush) / 10-20% (spray)
<b>APPLICATION SYSTEM</b>	
<b>Surface Preparation</b>	
New Surface	Allow the surfaces dry at least 2 days in case of speedy work or allow adequate time for surface to dry out completely. Surface must be free from efflorescence. Brush down or scrape off any loose material and cement splashes.
Old Surface	Powdery and chalky surfaces must be scrubbed and cleaned with water. Fungus and Mildew growth must be clean off with hypochlorite solution and allow for drying out at least 2-3 days.
<b>Coating system</b>	
Primer	Fresh concrete Surface: Apply 1-2 coats of Hato Super Quick Primer HA2037 (Solvent-based) New Surface: Apply 1-2 coats of Hato Alkali Resistant Primer HA2030 Old Surface: Apply 1-2 coats of Hato Contact Primer HA2033 (Water-based), HA2036 (Solvent-based)
Topcoat	Apply at least 2 coats of Hato Fiber cement Paint
<b>TIS</b>	-
<b>HANDLING AND STORAGE</b>	Keep the containers in a dry, cool, well ventilated space and away from heat. Containers must be kept tightly closed.
<b>HEALTH AND SAFETY</b>	Use under well ventilated conditions. Avoid skin contact.