

<b>FEATURES</b>	Camel Clear Lacquer is formulated from high-quality Nitro-Cellulose. It is suitable for the interior wood application. Paint film is fast-drying, gives high performance for decoration, high endurance quality, high gloss and highly adhesive with real wood and plywood with texture/grain. Non-mercuric and non-lead paints.
<b>TECHNICAL INFORMATION</b>	
Type	Nitro-Cellulose Lacquer
Color	Clear
Film appearance	Hi-Gloss
Pack size	5 Gallon
Solid by volume	30±2
Solid by weight	39±2%
Flash point	4
Specific gravity	0.90-1.00
Wet film thickness	70-80 Micron
Dry film thickness	20-25 Micron
Theoretical coverage	40-45 Sq.m./coat/gallon
	Remark - Actual Surface coverage will depend on surface irregularities, Mixing, Application Condition method and technique; as well as the structure and dimensions of the object to be coated
Touch dry (25-30°C)	4-6 Minutes
Recoat dry (25-30°C)	25-30 Minutes
Full cure (25-30°C)	2-3 Hours
<b>APPLICATION</b>	
Tools	Brush and Spray gun
Dilution (%)	Thinner 100-200%
<b>APPLICATION SYSTEM</b>	
<b>Surface Preparation</b>	
Old surfaces	Chalky surfaces or loose material must be removed by stiff brush. The surfaces must be clean and free of dirt, wax, salt, old paint and other contaminants
New surfaces	Use abrasive paper to sand the wood surface until smooth, fill all wood crack and hole by filler. Sand again until the smooth surface is obtained. The surfaces must be clean and free of dirt, grease, oil, wax, salt and other contaminants.
<b>Coating system</b>	
Primer	Apply CAMEL Sanding Sealer (CA3068) 1-2 Coat
Topcoat	Apply 2-3 coats of Camel Lacquer (Hi-Gloss) Flash off time between coat 5-10 minutes
<b>HANDLING AND STORAGE</b>	Keep the containers in a dry, cool, well ventilated space and away from heat. Containers must be kept tightly closed.
<b>HEALTH AND SAFETY</b>	Use under well ventilated conditions. Avoid skin contact.