

Technical Data Sheet

Hato Gold BJ-8008

Hato Acrylic Gold Paint Water-based

FEATURES	Hato Acrylic Gold Paint (Water-based) is made of 100% pure acrylic resin with premium golden pearl
	pigment suitable for exterior & interior application. The special quality golden pearl pigment that delivers
	rich & beautiful long lasting gold colours. Excellent adhesion, durable and can resist to harsh weathering
	conditions. Anti-fungus and algae. No lead and mercury added. Resistance against staining and
	blackening for 10 years.
TECHNICAL INFORMATION	
Туре	Acrylic Gold Paint water-based
Color	Emperor
Film appearance	Gloss
Pack size	1 Gallon, ¼ Gallon
Flash point	-
Wet film thickness	110-125 Microns
Dry film thickness	51.45-57.75 Microns
Theoretical coverage	30-35 Sq.m./coat/gallon
Touch dry (25-30°c)	30 Minutes
Recoat dry (25-30°c)	3-4 Hours
Full cure (25-30°c)	6 Hours
APPLICATION	
Tools	Brush (DO NOT USE ROLLER)
Diluent	TG-09 or Clean Water
Dilution (%)	10-20%
APPLICATION SYSTEM	
Surface Preparation	
New Surface	Allow adequate time for surface to dry out completely. Surface must be free from efflorescence. Brush
	down or scrape off any lose material and cement splashes.
Old Surface	Polish the surface with sandpaper to enhance better adhesion. Chalky or peeling surface must be
	thoroughly cleaned with water and leave completely dried. Apply 1-2 coats of Hato Contact primer.
Coating system	
Primer	Apply 1-2 coats of Hato Acrylic Primer for Gold paint (AG-11, AG-22, AG-33)
Topcoat	Apply at least 2-3 coats (Brush) of Hato Gold
TIS	-
HANDLING AND STORAGE	Keep the containers in a dry, cool, well ventilated space and away from heat. Containers must be kept
	tightly closed.
HEALTH AND SAFETY	Use under well ventilated conditions. Avoid skin contact.