

<b>FEATURES</b>	NOC (Primary colour), provides good adhesion and long-lasting durability. It is suitable for the decoration of masonry, primed plaster, concrete, concrete blocks, brickwork, cement render, ceilings, gypsum, and wood surfaces. Good algae resistance, no lead, and mercury added.
<b>TECHNICAL INFORMATION</b>	
Type	Emulsion paint
Color	Wide range of colours. Please refer to NOC Catalogue
Film appearance	Matt
Pack size	Bottle
Solid by volume	17.77-18.30
Solid by weight	27.35-28.17
Specific gravity	1.220-1.257
Wet film thickness	95-110 microns
Dry film thickness	16.88-19.55 microns
Theoretical coverage	30-40 Sq.m./coat/gallon
	Remark - Actual Surface coverage will depend on surface irregularities, Mixing, Application Condition method and technique; as well as the structure and dimensions of the object to be coated
Touch dry (25-30°C)	30 Minutes
Recoat dry (25-30°C)	2 Hours
Full cure (25-30°C)	At least 7 Days
<b>APPLICATION</b>	
Tools	Brush
Diluent	Clean Water
Dilution (%)	5-10%
<b>APPLICATION SYSTEM</b>	
<b>Surface Preparation</b>	
New Surface	Allow the surfaces dry at least 2 days in case of speedy work or allow adequate time for surface to dry out completely. Surface must be free from efflorescence. Brush down or scrape off any loose material and cement splashes.
Old Surface	Powdery and chalky surfaces must be scrubbed and cleaned with water. Fungus and Mildew growth must be clean off with hypochlorite solution and allow for drying out at least 2-3 days.
<b>Coating system</b>	
Primer	New concrete Surface: Apply 1-2 coats of NOC Super Primer TWO in one NO2012 (Water-based) Old Surface: Apply 1-2 coats of NOC Super Primer TWO in one NO2012 (Water-based)
Topcoat	Apply at least 2 coats of NOC Primary Colour Paint
<b>TIS</b>	-
<b>HANDLING AND STORAGE</b>	Keep the containers in a dry, cool, well ventilated space and away from heat. Containers must be kept tightly closed.
<b>HEALTH AND SAFETY</b>	Use under well ventilated conditions. Avoid skin contact.