

FEATURES	<p>NOC SUPER PRIMER 2 in 1 Water-based is made from special quality acrylic resin suitable for both exterior and interior applications. It is an ideal primer for new masonry surface where the alkalinity is like the cause of paint defect for the subsequent coating system. It effectively resists saponification on lime plaster, asbestos cement or concrete. Delivers strong adhesion, stain blocking, stain resistance, anti-fungus & algae and low odor. Pigmented primer provides outstanding high-hiding properties that help get the job done faster and with fewer coats of paint. Environmentally friendly with no-added lead and mercury.</p>
TECHNICAL INFORMATION	<p>Type Acrylic resin (Water-based)</p> <p>Color White</p> <p>Film appearance Sheen</p> <p>Pack size 5, 2.5 and 1 Gallons</p> <p>Solid by volume 30</p> <p>Solid by weight 47-50</p> <p>Specific gravity 1.340-1.395</p> <p>Wet film thickness 95-110 microns</p> <p>Dry film thickness 29-30 microns</p> <p>Theoretical coverage 35-40 Sq.m./coat/gallon</p> <p>Remark - Actual Surface coverage will depend on surface irregularities, Mixing, Application Condition method and technique; as well as the structure and dimensions of the object to be coated</p> <p>Touch dry (25-30°C) 30 Minutes</p> <p>Recoat dry (25-30°C) 2 Hours</p> <p>Full cure (25-30°C) At least 7 Days</p>
APPLICATION	<p>Tools Roller, Brush and Spray gun</p> <p>Dilution (%) NOC Super Primer Two in one is ready to use after through stirring. If thinning is necessary, dilute with clean water</p>
APPLICATION SYSTEM	<p>Surface Preparation</p> <p>New Surface Allow adequate time for surface to dry out completely. Surface must be free from efflorescence. Brush down or scrape off any loose material and cement splashes.</p> <p>Old Surface Powdery and chalky surfaces must be scrubbed and cleaned with water. Fungus and Mildew growth must be clean off with hypochlorite solution and allow for drying out at least 2-3 days.</p> <p>Coating system</p> <p>Primer Apply 1-2 coat of NOC Super Primer Two in one (NO2012)</p> <p>Topcoat Apply 1-2 coats of NOC Acrylic Emulsion Paint</p>
TIS	TIS 1123-2555 (Masonry Primer)
HANDLING AND STORAGE	Keep the containers in a dry, cool, well ventilated space and away from heat. Containers must be kept tightly closed.
HEALTH AND SAFETY	Use under well ventilated conditions. Avoid skin contact.