

## **Technical Data Sheet** Hato Super Contact Primer HA2036

FEATURES	HATO SUPER CONTACT PRIMER (Pigmented Primer) is made from special quality acrylic resin suitable for
TEATOREO	old concrete especially for chalking and loose or scaling paint. Delivers strong adhesion, stain blocking,
	stain resistance, anti-fungus & algae and low odor. Pigmented primer provides outstanding high-hiding
	properties that help get the job done faster and with fewer coats of paint. Environmentally friendly with no-
	added lead and mercury.
TECHNICAL INFORMATION	added load and morodry.
Type	Acrylic resin (Solvent-based)
Color	White
Film appearance	Matt
Pack size	5 and 1 US Gallons
Solid by volumn	25 ± 2
Solid by weight	48 ± 2
Flash point	37
	1.16-1.22
Specific gravity  Wet film thickness	75-100
	20-25
Dry film thickness	
Theoretical coverage	35-40 Sq.m./coat/gallon
	Remark - Actual Surface coverage will depend on surface irregularities, Mixing, Application Condition
T     (05.00° )	method and technique; as well as the structure and dimensions of the object to be coated 20-30 Minutes
Touch dry (25-30°c)	
Recoat dry (25-30°c)	2 Hours
Full cure (25-30°c)	1 Day
APPLICATION	
Tools	Roller, Brush
Dilution (%)	Hato Super Contact Primer is ready to use after through stirring. If thinning is necessary, dilute with
	Turpentine or White spirit 5-10% (roller and brush) / 100-150% (spray gun)
APPLICATION SYSTEM	
Surface Preparation	
New Surface	Allow the surfaces dry at least 2 days in case of speedy work or allow adequate time for surface to dry out
	completely. Surface must be free from efflorescence. Brush down or scrape off any lose material and
	cement splashes.
Old Surface	Powdery and chalky surfaces must be scrubbed and cleaned with water. Fungus and Mildew growth must
	be clean off with hypochlorite solution and allow for drying out at least 2-3 days.
Coating system	
Primer	Apply one coat of HATO Super Contact Primer (HA2036)
Topcoat	Can be topcoat with Acrylic Emulsion Paint and Alkyd Base Enamel Paint
TIS	-
HANDLING AND STORAGE	Keep the containers in a dry, cool, well ventilated space and away from heat. Containers must be kept
	tightly closed.
HEALTH AND SAFETY	Use under well ventilated conditions. Avoid skin contact.

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything only the quality of the product itself. We reserve the right to change the given data without notice.

Last update: August 2019

Page 1 of 1