

<b>FEATURES</b>	NEOTEX is emulsion Paint formulated with fungus and mould resistance with no lead and mercury added. It is ideal for the protection and decoration for masonry substrates such as plaster, concrete, brick, gypsum board. Good adhesion. Good algae resistance, no lead and mercury added.
<b>TECHNICAL INFORMATION</b>	
Type	100% Pure Acrylic Emulsion
Color	Wide range of colours. Please refer to NEOTEX Catalogue
Film appearance	Matt
Pack size	1 Gallons
Solid by volume	29.86-29.93
Solid by weight	50.07-50.70
Specific gravity	1.420-1.430
Wet film thickness	95-110 microns
Dry film thickness	28.43-32.92 microns
Theoretical coverage	30-40 Sq.m./coat/gallon
Touch dry (25-30°C)	30 Minutes
Recoat dry (25-30°C)	2 Hours
Full cure (25-30°C)	At least 7 Days
<b>APPLICATION</b>	
Tools	Roller, Brush and Spray
Diluent	Clean Water
Dilution (%)	5-10% (roller and brush) / 10-20% (spray)
<b>APPLICATION SYSTEM</b>	
<b>Surface Preparation</b>	
New Surface	Allow adequate time for surface to dry out completely. Surface must be free from efflorescence. Brush down or scrape off any loose material and cement splashes.
Old Surface	Powdery and chalky surfaces must be scrubbed and cleaned with water. Fungus and Mildew growth must be clean off with hypochlorite solution and allow for drying out at least 2-3 days.
<b>Coating system</b>	
Primer	New concrete Surface: Apply 1-2 coats of NOC Super Primer Two in one NO2012 (Water-based) Old Surface: Apply 1-2 coats of NOC Super Primer Two in one NO2012 (Water-based)
Topcoat	Apply at least 2 coats of NEOTEX Acrylic Emulsion Paint
<b>TIS</b>	-
<b>HANDLING AND STORAGE</b>	Keep the containers in a dry, cool, well ventilated space and away from heat. Containers must be kept tightly closed.
<b>HEALTH AND SAFETY</b>	Use under well ventilated conditions. Avoid skin contact.