

Technical Data Sheet

GPM Interior Emulsion Paint

FEATURES	GPM is emulsion Paint formulated with fungus and mould resistance with no lead and mercury added. It is
	ideal for the protection and decoration for interior masonry substrates such as plaster, concrete, brick,
	gypsum board. Good adhesion. Good algae resistance, no lead and mercury added.
TECHNICAL INFORMATION	
Туре	Emulsion paint
Color	White
Film appearance	Matt
Pack size	5 Gallons
Solid by volumn	28
Solid by weight	50-51
Specific gravity	1.429-1.487
Wet film thickness	95-110 micron
Dry film thickness	27-31 micron
Theoretical coverage	35-40 Sq.m./coat/gallon
	Remark - Actual Surface coverage will depend on surface irregularities, Mixing, Application Condition
	method and technique; as well as the structure and dimensions of the object to be coated
Touch dry (25-30°c)	30 Minutes
Recoat dry (25-30°c)	2 Hours
Full cure (25-30°c)	At least 7 Days
APPLICATION	
Tools	Roller, Brush and Spray
Diluent	Clean Water
Dilution (%)	5-10% (roller and brush) / 10-20% (spray)
APPLICATION SYSTEM	
Surface Preparation	
New Surface	Allow adequate time for surface to dry out completely. Surface must be free from efflorescence. Brush
	down or scrape off any lose material and cement splashes.
Old Surface	Powdery and chalky surfaces must be scrubbed and cleaned with water. Fungus and Mildew growth must
	be clean off with hypochlorite solution and allow for drying out at least 2-3 days.
Coating system	
Primer	New concrete Surface: Apply 1-2 coats of GPM Primer GP2060 (Water-based)
	Old Surface: Apply 1-2 coats of NOC Super Primer 2 in 1 NO2012 (Water-based)
Topcoat	Apply at least 2 coats of GPM Acrylic Emulsion Paint
TIS	-
HANDLING AND STORAGE	Keep the containers in a dry, cool, well ventilated space and away from heat. Containers must be kept
	tightly closed.
HEALTH AND SAFETY	Use under well ventilated conditions. Avoid skin contact.

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything only the quality of the product itself. We reserve the right to change the given data without notice.

Last update: August 2019