

FEATURES	HATO Varnish is suitable for all kinds of exterior & interior wood application. Paint film is smooth. Protects wood from UV light and highly resistant to any weather condition, prevent water penetration, fast-drying and light color to enhance the beauty of natural wood texture & grain. Suitable for wood structures such as house and boat as well as furniture. Not recommended for wood flooring and wood stair.
TECHNICAL INFORMATION	<p>Type Bituminus</p> <p>Color Black</p> <p>Film appearance Gloss</p> <p>Pack size ¼ and 1 Gallon</p> <p>Solid by volumn $41 \pm 2\%$</p> <p>Solid by weight $48 \pm 2\%$</p> <p>Specific gravity 0.88-0.93</p> <p>Flash point 16 c°</p> <p>Wet film thickness 90-100 Microns</p> <p>Dry film thickness 35-40 Microns</p> <p>Theoretical coverage 40-50 Sq.m./coat/gallon</p> <p>Remark - Actual Surface coverage will depend on surface irregularities, Mixing, Application Condition method and technique; as well as the structure and dimensions of the object to be coated</p> <p>Touch dry (25-30°C) 1-2 Hours</p> <p>Recoat dry (25-30°C) 6-8 Hours</p> <p>Full cure (25-30°C) 2-3 Days</p>
APPLICATION	<p>Tools Brush or Spray gun</p> <p>Diluent Turpentine or White Spirit</p> <p>Dilution (%) Brush 5-10% Spray gun 100-150%</p>
APPLICATION SYSTEM	<p>Surface Preparation</p> <p>New surface Use sandpaper to sand the wood surface until smooth Fill all wood crack and hole by filler Sand again until the smooth surface is obtained The surfaces must be clean and free of dirt, grease, oil, wax, salt, and other contaminants</p> <p>Old surface Chalky surfaces or loose material must be removed by stiff brush The surfaces must be clean and free of dirt, wax, salt, old paint, and other contaminants</p> <p>Coating system</p> <p>Primer -</p> <p>Topcoat Apply 1-2 coats of Hato Varnish</p>
HANDLING AND STORAGE	Keep the containers in a dry, cool, well ventilated space and away from heat. Containers must be kept tightly closed.
HEALTH AND SAFETY	Use under well ventilated conditions. Avoid skin contact.